

**Golight Radoray GL-2000-M Wireless Remote Control Spotlight - Handheld Remote - Magnetic**

Part #: GL-2000-M

**GOLIGHT COLOR: White****GOLIGHT REMOTE CONTROLLED LIGHT CAPABILITIES:**

- 370 degrees motorized rotation
- 140 degrees motorized tilt
- Fast/Slow speed options to improve positioning abilities

**GOLIGHT REMOTE CONTROLLED LIGHT OUTPUT:**

- Wireless remote control controls on/off of light beam
- Philips bulb - 12 Volts, 65 Watts
- Reflector—computer generated parabolic
- 5.5 amps draw
- 700 foot working beam (you can read a book at 700 feet)
- Candlepower - 5 million (new retail formula) or 400,000 (old industrial formula) [more on candlepower](#)

**BEAM:** Wide Spot beam - effective working beam of 700 feet (can read a book at 700 feet)**GOLIGHT REMOTE CONTROLLED WIRELESS REMOTE:**

- Wireless requires no wiring harness
- Effective to 150 feet (even through vehicles, walls, etc.)
- Operate on 433 mhz (works on radio signal, not IR, so line of site and obstructions are not an issue)
- Handheld remote included
- Remote is weatherproof
- 4 button operation - up/down, right/left
- Remote turns light on/off, so no additional switch required
- Programmable with 2187 channels
- Radio R.F. Frequency, F.C.C., S.A.E. tested and Canada Certified.

- Battery is MN21([GL-7921](#))

**GOLIGHT MATERIALS:**

- Housing-ASA Luran heat resistant, high impact, weather resistant housing with highest quality UV resistant material.
- Gears and transmission parts/engineering Lexan, and brass prevents rust, corrosion and oxidation that could impair performance.
- All connectors are weatherproof meet OEM vehicle manufacturer specifications
- Light gauge 16 foot wiring with multi-spring thin style cigarette plug.

**GOLIGHT 5 inch diameter 200lb. grip magnet**

Ideal for quick and easy installation and removal of unit. 200lb. magnet tested up to 85mph, this means, user can safely drive to speeds of up to 85mph without having to worry about the unit falling off. Magnetic base can be removed if you wish to install the remote control spotlight permanently

**GOLIGHT CUSTOMER SERVICE:**

- 3 year warranty on all Golight Radioray models.

**GOLIGHT REMOTE CONTROLLED LIGHT DIMENSIONS:**

- Golight base: 6"X 6"
- Height: 8 inches
- Independent Lab Tested to meet or exceed all S.A.E. Standards

**GOLIGHT CONDITIONS:**

- Golight meets marine standards for fresh water and saltwater usage
- UV and weatherproof for outdoor use
- Ambient temp: -28C (-20F) to 60C (140F)

[Click for GL-2XXX instructions](#)

[Click Here to see the Wiring Diagram for the GL-2020/2021 Models](#)

[Click Here for Long-Distance Spotlight Beam](#)

Part #: GL-2000-M (462)

